



EAST LAKE

Engineered



529 Oceanside

	US Units	Metric Units
Style Number	SA496	
Construction	Engineered	
Species	Maple	
Nominal Overall Thickness	3/8"	8.2 mm
Nominal Width	5"	127 mm
Maximum Length	Random lengths up to 58.5"	Random lengths up to 148.59 cm
Finish	Repel - Water Resist	
Gloss Level	40%	
Surface Texture	Scraped	
Edge Description	Pillowed	
End Description	PI	
Profile	Tongue And Groove	
Weight per Carton	35.5 lbs	16.1 kg
SQFT per Carton	23.66 sq ft	2.19 sq m
SQFT per Pallet	1419.6 sq ft	131.88 sq m
Installation Methods	Nail, Staple, Glue, Floating	
Installation Grade	Above, On, Below	
Variation	Moderate	
GREENGUARD® Certified	Yes	
Cradle-to-Cradle Certified	Yes	
Radiant Heat Approved	Yes	
Residential Warranty	Repel Hardwood Lifetime	
Commercial Warranty	5 Years	
Installation	Repel Water Resistant Hardwood Flooring Installation Guidelines	
Maintenance	Hardwood Maintenance Guidelines	
All measurements are nominal.	Cartons may include random lengths.	

Features

Subtle scraped maple flooring in bold, rich colors. Also available in a smooth surface version, Clearwater.

Suggested Adhesive

Style Name	Style Number
35MC	HS105
Urebond Plus	SWADH

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



SRH38

Flush Reducer



SORH8

*Overlap Reducer



SSH38

Flush Stairnose



SOSH8

*Overlap Stairnose



SCH38

Threshold / Carpet Reducer



TMH78

T-Molding



QTR96

Quarter Round

Trim images are for illustration purposes only. Actual dimensions will vary. Contact the Shaw Information Center for additional details: 800-441-7429.



MADE IN THE USA


EAST LAKE



Colors




460 Surfside




493 Bayfront



529 Oceanside




627 Burnside



698 Conway



1023 Crescent Beach



5034 Windsurf