

HARDWOOD

FIFTH AVENUE OAK

Engineered



5014 Roosevelt

	US Units	Metric Units
Style Number	SW663	
Construction	Engineered	
Species	White Oak	
Nominal Overall Thickness	1/2"	12 mm
Nominal Width	4.72"	119.89 mm
Maximum Length	23.62"	59.99 cm
Finish	UV Aluminum Oxide	
Gloss Level	7%	
Surface Texture	Wirebrushed	
Edge Description	Micro Bevel	
End Description	Mb	
Profile	Tongue And Groove	
Weight per Carton	45 lbs	20.41 kg
SQFT per Carton	27.9 sq ft	2.59 sq m
SQFT per Pallet	892.8 sq ft	82.94 sq m
Installation Methods	Glue	
Installation Grade	Above, On, Below	
Variation	High	
GREENGUARD® Certified	Yes	
Cradle-to-Cradle Certified	Yes	
Radiant Heat Approved	No	
Residential Warranty	50 Year Shaw Hardwood Limited Residential Warranty	
Commercial Warranty	5 Year Commercial	
Installation	Engineered Hardwood Installation Guidelines	
Maintenance	Shaw Hardwood Maintenance	
All measurements are nominal.	Cartons may include random lengths.	

Suggested Adhesive

Style Name	Style Number
3-in-1 Ultra	111SA
35MC	HS105

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



SRH12

Flush Reducer



SSH12

Flush Stairnose



SCH12

Threshold / Carpet Reducer



TMH78

T-Molding



QTR96

Quarter Round

Trim images are for illustration purposes only. Actual dimensions will vary. Contact the Shaw Information Center for additional details: 800-441-7429.


FIFTH AVENUE OAK

HARDWOOD

Colors



1007 Astor



1028 Carnegie



5014 Roosevelt