

LUXURY VINYL

PRIME PLANK
vinyl plank



717 Tattered Barnbo

	US Units	Metric Units
Style Number	0616V	
Construction	Residential Resilient LVT-Drybac<=2Mm	
Profile	Direct Glue	
Size	7" x 48"	17.78 cm x 121.92 cm
Overall Thickness	0.079"	2 mm
Wear Layer Thickness	6 mil (0.006")	0.2 mm
Finish	Opticlean Urethane	
Edge Description	Square	
Area per Carton	51.33 sq ft	4.77 sq m
Area per Pallet	2566.5 sq ft	238.44 sq m
Installation Methods	Direct Glue	
Installation Grade	Above, On, Below	
Residential Warranty	15 Year Residential Resilient Limited Warranty	
Installation	Residential Resilient Direct Glue Installation Guidelines	
Maintenance	Residential Resilient Maintenance	

Colors



Suggested Adhesive

Style Name	Style Number
SHAW 200 1 GAL	052VS
KWIKFLASH 4 GAL	080VS
KWIKFLASH LV 1	081VS
S150 SPRAY ADHS	069VS
SHAW 200 TPS 4G	026VS

Coordinating Trim



Omni Trim*
VSUN1 | 94"






Quarter Round
VSQT1 | 94"



Overlap Stairnose*
VSSN1 | 94"

*Packaged with molding track

Coordinating Metal Trim



Finish	Reducer	T-Mold	Stair Cap
Satin Silver	152SA	155SA	149SA
Satin Nickel	153SA	156SA	150SA
Dark Bronze	157SA	151SA	

Installation Range

Profile Size	Installation Range
3.5mm	1.5mm to 3.5mm heights
5.5mm	3.6mm to 5.5mm heights
8mm	6mm to 8mm heights