



# SANCTUARY OAK

Engineered



6006 Fireside

# SANCTUARY OAK



|                                  | US Units  | Metric Units                   |
|----------------------------------|---|--------------------------------|
| <b>Style Number</b>              | <b>SW714</b>  |                                |
| <b>Construction</b>              | Engineered  |                                |
| <b>Species</b>                   | Oak   |                                |
| <b>Nominal Overall Thickness</b> | 1/2"  | 12 mm                          |
| <b>Nominal Width</b>             | 6.38"   | 162.05 mm                      |
| <b>Maximum Length</b>            | Random lengths up to 58.56"   | Random lengths up to 148.74 cm |
| <b>Finish</b>                    | Repel - Water Resist  |                                |
| <b>Gloss Level</b>               | 7%  |                                |
| <b>Surface Texture</b>           | Wirebrushed   |                                |
| <b>Edge Description</b>          | Micro Bevel   |                                |
| <b>End Description</b>           | Mb  |                                |
| <b>Profile</b>                   | Tongue And Groove   |                                |
| <b>Weight per Carton</b>         | 61 lbs  | 27.66 kg                       |
| <b>SQFT per Carton</b>           | 25.4 sq ft  | 2.35 sq m                      |
| <b>SQFT per Pallet</b>           | 990.6 sq ft   | 92.02 sq m                     |
| <b>Installation Methods</b>      | Nail, Staple, Glue, Floating  |                                |
| <b>Installation Grade</b>        | Above, On, Below  |                                |
| <b>Variation</b>                 | High  |                                |
| <b>Ortho-Phthalates Free</b>     | Yes   |                                |
| <b>Radiant Heat Approved</b>     | Yes   |                                |
| <b>Residential Warranty</b>      | Repel Hardwood Lifetime   |                                |
| <b>Commercial Warranty</b>       | 5 Year Commercial   |                                |
| <b>Installation</b>              | <a href="#">Repel Water Resistant Hardwood Flooring Installation Guidelines</a> |                                |
| <b>Maintenance</b>               | <a href="#">Hardwood Maintenance Guidelines</a>                                 |                                |
| <b>Regional Availability</b>     | Not Available in Canada   |                                |
| All measurements are nominal.    | Cartons may include random lengths.   |                                |

## Features

Find your sanctuary at home with this gorgeous oak hardwood from Shaw Floors. This style is part of the REPEL Collection with Splash-Proof Technology that guards against splashes and spills 2x better than untreated hardwood. It also features superior dent resistance and ScufResist® Platinum finish to guard against scuffs.

## Suggested Adhesive

| Style Name   | Style Number |
|--------------|--------------|
| 35MC         | HS105        |
| Urebond Plus | SWADH        |

**Trim Pieces** length: 78" (\*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



**SRH12**

Flush Reducer



**SORH2**

\*Overlap Reducer



**SSH12**

Flush Stairnose



**SOSH2**

\*Overlap Stairnose



**SCH12**

Threshold / Carpet Reducer



**TMH78**

T-Molding



**QTR96**

Quarter Round



MADE IN THE USA


Trim images are for illustration purposes only. Actual dimensions will vary. Contact the Shaw Information Center for additional details: 800-441-7429.



# SANCTUARY OAK



## Colors



1088 Serenity



1089 Haven



5093 Hearth



6006 Fireside