



1074 Limestone

|                                   | US Units                                                                        | Metric Units                   |
|-----------------------------------|---------------------------------------------------------------------------------|--------------------------------|
| <b>Style Number</b>               | <b>SW705</b>                                                                    |                                |
| <b>Construction</b>               | Engineered                                                                      |                                |
| <b>Species</b>                    | White Oak                                                                       |                                |
| <b>Nominal Overall Thickness</b>  | 3/8"                                                                            | 8.2 mm                         |
| <b>Nominal Width</b>              | 6.38"                                                                           | 162.05 mm                      |
| <b>Maximum Length</b>             | Random lengths up to 58.56"                                                     | Random lengths up to 148.74 cm |
| <b>Finish</b>                     | Repel - Water Resist                                                            |                                |
| <b>Gloss Level</b>                | 20%                                                                             |                                |
| <b>Surface Texture</b>            | Smooth                                                                          |                                |
| <b>Edge Description</b>           | Micro Bevel                                                                     |                                |
| <b>End Description</b>            | Mb                                                                              |                                |
| <b>Profile</b>                    | Tongue And Groove                                                               |                                |
| <b>Weight per Carton</b>          | 47 lbs                                                                          | 21.31 kg                       |
| <b>SQFT per Carton</b>            | 30.48 sq ft                                                                     | 2.83 sq m                      |
| <b>SQFT per Pallet</b>            | 1371.6 sq ft                                                                    | 127.42 sq m                    |
| <b>Installation Methods</b>       | Nail Down, Floating, Staple, Glue                                               |                                |
| <b>Installation Grade</b>         | Above, On, Below                                                                |                                |
| <b>Variation</b>                  | High                                                                            |                                |
| <b>GREENGUARD® Certified</b>      | Yes                                                                             |                                |
| <b>Cradle-to-Cradle Certified</b> | Yes                                                                             |                                |
| <b>Radiant Heat Approved</b>      | Yes                                                                             |                                |
| <b>Residential Warranty</b>       | Repel Hardwood Lifetime                                                         |                                |
| <b>Commercial Warranty</b>        | 5 Years                                                                         |                                |
| <b>Installation</b>               | <a href="#">Repel Water Resistant Hardwood Flooring Installation Guidelines</a> |                                |
| <b>Maintenance</b>                | <a href="#">Hardwood Maintenance Guidelines</a>                                 |                                |
| All measurements are nominal.     | Cartons may include random lengths.                                             |                                |

## Features

With a smooth texture and microbevel edge profile, Villa let's the natural beauty of white oak shine through.

## Suggested Adhesive

| Style Name   | Style Number |
|--------------|--------------|
| 35MC         | 119BA        |
| Urebond Plus | HWADH        |

**Trim Pieces** length: 78" (\*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



**SFR18**

Flush Reducer



**SR018**

\*Overlap Reducer



**SFS18**

Flush Stairnose



**SSO18**

\*Overlap Stairnose



**SCR18**

Threshold / Carpet Reducer



**SWTM8**

T-Molding



**SQTR8**

Quarter Round

Trim images are for illustration purposes only. Actual dimensions will vary. Contact the Shaw Information Center for additional details: 800-441-7429.




MADE IN THE USA

## Colors




1069 Quartz



1074 Limestone




2046 Sand



5078 Pebble



7051 Shale



7061 Basalt