

7362 Vickery Creek

	US Units	Metric Units
Style Number	3059V	
Construction	Manufactured SPC Residential	
Profile	Fold-N-Tap	
Size	7" x 48"	17.78 cm x 121.92 cm
Overall Thickness	0.197"	5 mm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Attached Underlayment	XPO Pad	
Attached Underlayment Thickness	0.039"	1 mm
Finish	ScuffResist Platinum	
Edge Description	Micro Bevel	
Area per Carton	21.27 sq ft	1.98 sq m
Area per Pallet	1701.6 sq ft	158.08 sq m
Installation Methods	Floating	
Installation Grade	Above, On, Below	
Residential Warranty	Residential Resilient Lifetime Limited Warranty	
Installation	Floorte Pro 3 & 5 Installation Guidelines	
Maintenance	Residential Resilient Maintenance	
Smoke Density (ASTM E662, Flaming Mode)	Passes, <450	
Radiant Panel (ASTM E648)	Passes, Class I	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Colors



Coordinating Trim




Baby Threshold*

BT3NS | 94"



T-Molding*

TM3NS | 94"



Multi-Purpose Reducer

RD3NS | 94"



Quarter Round

QTRNS | 94"



Flush Stairnose

FS4NS | 94"

*Packaged with molding track