



6053 Ember

	US Units	Metric Units
<b>Style Number</b>	<b>VE504</b>	
<b>Construction</b>	Residential Resilient LVT-Drybac<=2Mm	
<b>Profile</b>	Direct Glue	
<b>Size</b>	7" x 48"	17.78 cm x 121.92 cm
<b>Overall Thickness</b>	0.079"	2 mm
<b>Wear Layer Thickness</b>	12 mil (0.012")	0.3 mm
<b>Finish</b>	ArmourBead®	
<b>Edge Description</b>	Square	
<b>Area per Carton</b>	51.33 sq ft	4.77 sq m
<b>Area per Pallet</b>	2566.5 sq ft	238.44 sq m
<b>Installation Methods</b>	Direct Glue	
<b>Installation Grade</b>	All Levels of the Home	
<b>Environmental</b>	FloorScore® Certified	
<b>Residential Warranty</b>	<a href="#">25 Year Residential Resilient Limited Warranty</a>	
<b>Installation</b>	<a href="#">Residential Resilient Direct Glue Installation Guidelines</a>	
<b>Maintenance</b>	<a href="#">Residential Resilient Maintenance</a>	
<b>Smoke Density (ASTM E662, Flaming Mode)</b>	Passes, <450	
<b>Radiant Panel (ASTM E648)</b>	Passes, Class I	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Colors





**Coordinating Trim**



**Omni Trim\***  
OMNMB | 94"



**Quarter Round**  
QTRMB | 94"



**Overlap Stairnose\***  
OOLMB | 94"

\*Packaged with molding track