



2097 Flaxen

	US Units	Metric Units
Style Number	375MF	
Construction	Residential Resilient LVT-Drybac<=2Mm	
Profile	Direct Glue	
Size	7" x 48"	17.78 cm x 121.92 cm
Overall Thickness	0.079"	2 mm
Wear Layer Thickness	12 mil (0.012")	0.3 mm
Edge Description	Square	
Area per Carton	51.33 sq ft	4.77 sq m
Area per Pallet	2566.5 sq ft	238.44 sq m
Installation Methods	Direct Glue	
Installation Grade	All Levels of the Home	
Environmental	FloorScore® Certified	
Residential Warranty	Residential Resilient Limited Warranty - Defects 15 Years	
Commercial Warranty	5 Year Light Commercial	
Installation	Installation Guidelines for Luxury Vinyl Plank and Tile	
Smoke Density (ASTM E662, Flaming Mode)	Passes, <450	
Radiant Panel (ASTM E648)	Passes, Class I	

Features

Limitless II lives up to its name. This 12 mil is available in all colors from your spec level needs including sheet, 8 mil, 20 mil, Loose Lay, SPC, and Limitless 5mm w/acoustical pad

Colors



Coordinating Trim



Omni Trim*
OMNMB | 94"



Quarter Round
OQRMB | 94"



Overlap Stairnose*
OOLMB | 94"

*Packaged with molding track