



7315 Smoky Taupe

	US Units	Metric Units
Style Number	376MF	
Construction	Residential Resilient LVT-Drybac<=2Mm	
Profile	Direct Glue	
Size	7" x 48"	17.78 cm x 121.92 cm
Overall Thickness	0.098"	2.5 mm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Edge Description	Square	
Area per Carton	35 sq ft	3.25 sq m
Area per Pallet	2100 sq ft	195.1 sq m
Installation Methods	Direct Glue	
Installation Grade	All Levels of the Home	
Residential Warranty	Residential Resilient Limited Warranty - Defects, Wear	
Commercial Warranty	10 Year Light Commercial	
Installation	Installation Guidelines for Luxury Vinyl Plank and Tile	
Smoke Density (ASTM E662, Flaming Mode)	Passes, <450	
Radiant Panel (ASTM E648)	Passes, Class I	

Features

Limitless II lives up to its name. This 20 mil is available in all colors from your spec level needs including sheet, 8 mil, 12 mil, Loose Lay, SPC, and Limitless 5mm w/acoustical pad

Colors



Coordinating Trim



Omni Trim*

OMNMB | 94"



Quarter Round

OQRMB | 94"



Overlap Stairnose*

OOLMB | 94"

*Packaged with molding track